

ShineVision



Features

- ▶ RF communication for wireless operation.
- ▶ Automatic monitoring of up to six inverters simultaneously, applicable for small home system.
- ▶ Simple installation. It can be placed anywhere indoor with signal coverage.
- ▶ Easy-to-understand data display by simple key operation: real-time power, three-phase AC voltage, PV voltage, daily, monthly and total power yield and income, temperature, light intensity, the date and time.
- ▶ Data archiving automatically and permanently with high security.
- ▶ Audio alarm in the event of errors.
- ▶ Low power consumption, powered by adaptor or battery.

GROWATT NEW ENERGY CO., LTD

A: No. 12 Building, Xicheng Industrial Zone, Bao'an District, Shenzhen, P. R.China
T : + 86 755 2747 1900 F : + 86 755 2749 1460 E : service@ginverter.com

Communication

Inverter communication	Wireless radio frequency
Number of inverters	Max.6 units

Communication range

Partition communication	Max.30m
-------------------------	---------

Power supply

Power supply	Adapter
Type of battery	#7 AAA alkaline battery

Environmental conditions for operation

Emitter temperature	-10 °C ~ 60 °C
Monitor temperature	-10 °C ~ 50 °C
Humidity range	≤80%
Protection rating	IP20

General Data

Dimensions (W / H / D) in mm	78/118/52
Weight	120g
Installation site	Indoor
Deployment options	Desktop device
Language versions	English

Features

Display	LCD display
Operation	key-press
Warranty	13 months

Information displayed

General Information	Time, date, temperature
System Data	Three-phase AC voltage, PV voltage, real time power, daily yield, monthly yield, total yield, income