## Ei3016



### Optical Smoke Alarm



- Optical sensor quick response to slow smouldering fires
- Mains powered with Rechargeable Lithium Back-up
- Built in AudioLINK+ data extraction technology
- Easi-fit base for quick and simple installation
- Kitemarked to BS EN14604:2005





#### Description

The Ei3016 is a mains powered Optical Smoke Alarm with 10 Year Rechargeable Lithium Back-up. It contains built-in AudioLINK+ data extraction technology and is upgradeable to SmartLINK wireless interconnection using a Ei3000MRF module

#### **General Information**

Battery Type	Lithium rechargeable	Battery weight (kg)	0.009
Depth (mm)	63	Fixings	Screws included
Humidity Range (%)	15-95	Indicators	Green - Power / Red - Alarm / Yellow - Fault
Kitemark reference	522831	Luckins TSI Code	405601570
Material	HIP UL94 V0 Flame retardant	Outer paper/cardboard weight (kg)	0.038
Packaged weight (kg)	0.383	Paper/cardboard weight (kg)	0.062
Plastic weight (kg)	0.002	Sensor Type	Optical - with dust compensation
Supply Voltage (V)	230	Power Consumption (W)	0.25
Product weight (kg)	0.332	Technologies	AudioLINK+
Temperature Range (°C)	-10 to 40	Voltage Type	AC
Warranty	5 year warranty	Width (mm)	150
Technical			

# Sensor TypeOptical - with dust compensationIndicatorsGreen - Power / Red - Alarme ellow -<br/>FaultSupply Voltage (V)230Voltage TypeACBattery TypeLithium rechargeablePower Consumption (W)0.2F

an 🗐 Company



#### Technologies

AudioLINK+

#### **Dimensions & Weights**

Depth (mm)	63	Height (mm)	150		
Width (mm)	150	Product weight (kg)	0.332		
Packaged weight (kg)	0.383				
Approvals & Warranty					
<b>Certification/Approvals</b>	BS EN 14604:2005	Warranty	5 year warranty		
EAN Number	5099383006513				
Environmental					
Humidity Range (%)	15-95	Temperature Range (°C)	-10 to 40		

01691 664100 enquiries@aico.co.uk

www.aico.co.uk

Company Registration No.: 2544399 WEEE Registration No.: WEE/AE0109WY Battery Producer Registration No.: BPRN00307

an 🗐 Company