

EV Charger





Plug and Play

Fast and easy installation. Monitor your Smart
System on the move via our GivEnergy
Monitoring Portal and App.



App Controlled

Control your vehicle's charge via the GivEnergy Monitoring Portal and App. Manage your settings or set a schedule



Integrated PEN Protection

No Earth rod required for installation



Charge your vehicle from excess solar generation.

Charge your electric vehicle in no time with GivEnergy's fast and reliable 7kW EV Charger.

The EV Charger is a new member of the GivEnergy family. Compatible with most plug-in electric cars, the EV charger is a great addition to your smart home system and GivEnergy eco-system. It's compact and waterproof design allows for installation in tight spaces, indoor and outdoor. Integrated WiFi allows for easy control of your vehicle's charge via the GivEnergy Monitoring Portal or App.

Dimensions (HxDxW)

310 x 95 x 220 (mm)

Wallbox

1.85kg

Wallbox + Cable

3.85kg

Connectivity

LAN (RJ-45), WiFi and 4G

Cable Length

5m

TECHNICAL SPECIFICATIONS

MODEL		GivEnergy EV Charger	
Power Specification			
AC Power Input Rating		IEC Standard	
		1-phase	
		230V <u>±</u> 15%	
AC Power Output Rating		7kW / 32A	
Rated Frequency		50 / 60Hz	
MCB Protection (required)		32A Double Pole	
AC Connection		3 Wire - Live/Neutral/Earth	
Connector Type		IEC 62196-2 (Type 2)	
Connector Mechanical Operating Life		≥10000 times	
User Interface & Control			
Charging Control		Plug and Play, RFID Card, or App	
LED Display		4 LED indicators (Power/WiFi/Charging/Fault)	
Connectivity		LAN (RJ-45), Wi-Fi and 4G	
Charger Protocol		OCPP 1.6J	
Environmental			
Storage Temperature		-40 to 75°C ambient	
Operating Temperature		-30 to 55°C ambient	
Operating Humidity		Up to 95% non-condensing	
Altitude		≤2000m	
Cooling Method		Natural Cooling	
Protection			
Protection Ratings	IP65	Type B RCD Build-in	Yes
Over Voltage Protection	Yes	Under Voltage Protection	Yes
Over Load Protection	Yes	Short Circuit Protection	Yes
Earth Leakage Protection	Yes	Ground Protection	Yes
Over Temp Protection	Yes	Surge Protection	Yes
Wallbox			
Dimensions (HxWxD)		310 x 220 x 95 (mm)	
Wallbox Weight		1.85kg	
Wallbox Weight + Cable		3.85kg	
Charging Cable Length		5m	
Enclosure Material		PC + ASA	