Panasonic

N 295



Product

Guarantee

years

Photovoltaic module HIT[®] VBHN295SJ46

Only 1.46 m tall

More power on your roof thanks to best fit in portrait due to shorter module length and less space between module rows on flat roofs.



100% Panasonic, 100% HIT

Proudly featuring Panasonic's original invention, the heterojunction solar cell. With over 1 billion cells produced commercially over 20 years, 25 years after the breakthrough in the development and looking back to over 40 years of experience in solar, Panasonic really offers you a 25-year guarantee you can trust.

	r business since 1975
	heterojunction technology since 1990
	HIT mass-production since 1997
19	



Unique

water drainage

www.eu-solar.panasonic.net




Photovoltaic module HIT°


N295

E

Max. power (Pmax) [W]	295
Voltage at Max. Power (Vmp)(V)	52.7
Current at Max. Power (Imp)(A)	5.60
Open circuit voltage (Voc) [V]	63.7
Short circuit current (Isc) [A]	6.00
Max. over current rating [A]	15
Power tolerance [%] *	+10/-0
Max. system voltage [V]	1000
Solar panel efficiency (%)	19.1
Note: Standard Test Conditions: Air mass 1.5; Irradiance = 1 [†] Maximum power at delivery. For guarantee conditions, pl	
Temperature characteristics	
Temperature (NOCT) [°C]	44.0
Temp. coefficient of Pmax [%/°C]	-0.258
Temp. coefficient of Voc [V/°C]	-0.150
Temp. coefficient of lsc [mA/°C]	3.30
At NOCT (Normal Operating Conditions)	
Max. power (Pmax) [W]	225.8
Max. power voltage (Vmp) [V]	50.9
Max. power current (Imp) [A]	4.50
Open circuit voltage (Voc) [V]	60.4
Short circuit current (lsc) [A]	4.85
Note: Normal Operating Cell Temp.: Air mass 1.5; Irradiance Air temperature 20°C; wind speed 1 m/s	= 800W/m²;
At low irradiance (20%)	
Max. power (Pmax) [W]	56.8
Max. power voltage (Vmp) [V]	51.5
Max. power current (Imp) [A]	1.11
Open circuit voltage (Voc) [V]	59.7
Short circuit current (lsc) [A]	1.20







Guarantee

Power output:	10 years (90% of Pmin) 25 years (80% of Pmin)			
Product workmanship:	25 years (registration necessary on www.eu-solar.panasonic.net, otherwise 15 years apply based on guarantee document)			
Materials				
Cell material:	5 inch photovoltaic cells			
Glass material:	AR coated tempered glass			
Frame materials:	Black anodized aluminium			
Connectors type:				

Certificates

CLASS UNO By TÜV Rheinland UNI 8457 UNI 9174 UNI 9177



ical Protectio

CE

Please consult your local dealer for more information

JET

IEC61215

IEC61730-1

IEC61730-2

A CAUTION! Please read the installation manual carefully before using the products.

Used electrical and electronic products must not be mixed with general household waste. For proper treatment, recovery and recycling of old products, please take them to applicable collection points in accordance with your national legislation.

Panasonic

X

Panasonic Electric Works Europe AG Robert-Koch-Straße 100, 85521 Ottobrunn, Germany Tel. +49 89 45354-1000 Fax +49 89 45354-2111

Panasonic Eco Solutions Europe

info.solar@eu.panasonic.com