

No.:

VERIFICATION OF COMPLIANCE

Applicant: Shenzhen SOFAR SOLAR Co., Ltd
401, Building 4, AnTongDa Industrial Park, District 68,

GZES1901010700PV

XingDong Community, XinAn Street, BaoAn District, Shenzhen

City, Guangdong Province, P.R. China

Manufacturer: Shenzhen SOFAR SOLAR Co., Ltd

401, Building 4, AnTongDa Industrial Park, District 68,

XingDong Community, XinAn Street, BaoAn District, Shenzhen

City, Guangdong Province, P.R. China

Product Name: Solar Grid-tied Inverter

Product Description: Grid connected photovoltaic inverter

Model No.: SOFAR 3KTLM-G2

Trade Mark:

5 FAR

Intended Use: PV system

Rating:

See page 2

Additional Information (if any): IP 65, Class I

Software version: V0.22

Sufficient samples of the product have been tested and found to be in conformity with

Test Standard: Engineering Recommendation G98 Issue 1 – Amendment 1

16 May 2018

as shown in the

Test Report Number(s): GZES190101070001

This Verification of Compliance has been granted to the applicant based on the results of tests, performed by Laboratory of SGS-CSTC Standards Technical Services Co., Ltd. on sample of the above-mentioned product in accordance with the provisions of the relevant specific standards.

Roger Hu

Technical Manager

SGS-CSTC



Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.



No.: **GZES1901010700PV**

Other information added:

Rating:

| Product Model | SOFAR 3KTLM-G2 |
|-----------------------------|----------------------|
| Input (DC) | |
| Max.DC Input Power | 3500W |
| Max.DC Voltage | 600V |
| Power Turn on | 80V |
| Start-up input voltage | 120V |
| Rated input voltage | 360V |
| MPPT Voltage Range | 90-580V |
| Full load DC voltage range | 160-520V |
| MAX input current per MPPT | 11A/11A |
| Number of DC inputs | 2/2 |
| Output(AC) | |
| Max AC Output power | 3000VA |
| Max AC Output power (PF=1) | 3000W |
| Max AC Output Current | 13.7A |
| Nominal Grid Voltage | 230Vac(Single phase) |
| Nominal Frequency | 50Hz |
| Power factor | 1(adjustable+/-0.9) |
| Topology | Transformerless |
| Operating temperature range | -25-60°C |
| Degree of protection | IP65 |

Regula





Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.