

## **SolarEdge Modbus Meter**

SE-WNC-3Y400-MB-K1



## **Modbus Meter for SolarEdge Installations**


- High accuracy meter readings for production/consumption monitoring
- Import/Export meter readings for export limitation functionality
- Small and easy to install fits in standard electrical panel
- Supports residential, commercial and utility-size installations




When ordering a meter, order current transformers as well:


CURRENT TRANSFORMER MODELS(*)	RATED RMS CURRENT	DIMENSIONS (INTERNAL/ EXTERNAL)
SE-ACT-0750-50	50 A	
SE-ACT-0750-100	100 A	20 x 20 mm / 61 x 60.4 mm
SE-ACT-0750-250	250 A	
SE-CTS-2000-1000	1000 A	50.8 x 50.8 mm / 121 x 127 mm

<sup>\*</sup> One current transformer per phase; for other ratings contact SolarEdge



## 2.40 (61.0) 0.90 (22.9)





	SE-WNC-3Y400-MB-K1	UNITS
ELECTRICAL SERVICE		
Operating Voltage Range - Line to Neutral / Line to Line	184-264.5 / 320-460	Vac
AC Frequency	50/60	Hz
Grids Supported - Single Phase ; Three Phase*	L / N / PE ; L1 / L 2 / L3 / N / PE	
Power Consumption (typ.)	1.8	W
COMMUNICATION		
Supported Communication Interfaces	RS485	
Response time	≤1**	sec
Default Device ID (Modbus)	2	
ACCURACY (@25°C, PF:0.7- 1)***		
1% - 100% of Rated CT Current	±1.5	%
STANDARD COMPLIANCE		
Safety	IEC 61010-1	
Immunity	EN 61326, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-11	
Emissions	EN 55022 Class B	
INSTALLATION SPECIFICATIONS		
Dimensions (HxWxD)	85 x 153 × 38	mm
Weight	310	
Enclosure type	High impact, ABS and/or ABS/PC plastic UL 94V-0, IEC FV-0	
Operating Temperature Range	-30 to 55	°C
Relative Humidity (noncondensing)	5 - 90	%
Protection Rating	Indoor (Outdoor when installed in an outdoor enclosure)	
Mounting Type	DIN Rail / Wall mount	



<sup>\*</sup> PE (Protective Earth) connection is not required for meter operation
\*\* When meter is connected at grid connection point, and when RS485 is used for multiple inverters

<sup>\*\*\*</sup> Using ACT-0750 CT models